

NON HAZARDOUS - CHEMICAL IDENTIFICATION CODE NOT APPLICABLE

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY UNDERTAKING:

Product Name : COLORTEC POXY PART A

HS CODE : 32149000

Application:High performance epoxy grout for tilesManufacturer:MATEX CONSTRUCTION CHEMICALS

MANUFACTURING CO. L.L.C.

 Address
 :
 P.O. Box 29585

 Telephone
 :
 +971 4 3334140

 Fax
 :
 +971 4 3334115

 Email
 :
 info@matex.ae

Website : www.matex-global.com

2. HAZARDS IDENTIFICATION:

Hazard Designation : Xi Irritant

Risk Phrase(s) : R36/38, Irritating to eyes and skin

: R43, May cause sensitization by skin contact

Safety Phrase(s) : S37/39, Wear suitable gloves and eye/face protection

: S51, Use in a well-ventilated area

3. COMPOSITION / INFORMATION ON INGREDIENTS:

Ingredients	% Composition	CAS No.	
Epoxy resin	85-90	90598-46-2	
Titanium dioxide	8-12	13463-67-7	
Additive	0.4	64742-47-8	

4. FIRST AID MEASURES:

Skin contact : Flush with large amounts of clean water, use soap if

available. Remove any contaminated clothing.



Eye contact : Check for and remove any contact lenses. Flush with

large amounts of clean warm water for 15 minutes. Get

prompt medical attention.

Inhalation : Immediately move victim to fresh air. If breathing has

stopped then administer artificial respiration. Get

prompt medical attention.

Ingestion : Not a normal route of injury. Do not induce vomiting;

give large quantities of water, get immediate medical attention. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquids into lungs. Do not give anything by mouth to an unconscious

person.

5. FIRE FIGHTING MEASURES:

Hazardous Combustion Products : Carbon dioxide, phenolic

Firefighting Measures : Foam, carbon dioxide, dry chemical. Wear protective

equipment including self-contained apparatus.

6. ACCIDENTAL RELEASE MEASURES:

Method and Materials for Clean Up : Spill should be contained by bundling and absorbing with

dry inert filler (e.g. vermiculite, sand, oil etc), which can be shoveled into appropriately labeled drums. Disposal

should be effected by approved waste disposal organization according to local regulations.

Environmental Precautions : Avoid subsoil penetration. Do not allow to enter into

drains, sewers or waterways.

7. HANDLING AND STORAGE:

Precautions for Safe Handling : Wear personal protective equipment (PPE) as per Sec.8.

Conditions for Safe Storage : Keep containers tightly closed; store under cool dry

conditions. Keep away from food and drink. Keep out of reach of children. Store under cover and away from direct sunlight and moisture. Store at 5°C to 35°C. Keep

away from incompatible materials.



8. EXPOSURE CONTROLS / PERSONAL PROTECTION:

Engineering Controls : Ventilation is recommended under normal use

conditions. State regulations on speed and direction of airflow away from operators must be observed. Keep

containers closed when not in use.

Exposure Standards : None established for this product.

Personal Protective Equipment (PPE):

Respiratory protection : Type A1 if ventilation is inadequate

Glove type (AS2161) : Chemical resistant, impervious gloves e.g. PVC, butyl

rubber or nitrile rubber gauntlets (consult your local

glove supplier/manufacturer).

Eye Protection : Chemical worker's goggles or well-fitting safety glasses

or full face shield.

Clothing : No special clothing required but overalls or other

suitable industrial clothing which provides full skin coverage are suggested as a general precaution, especially where heavy contamination is likely.

Other : Use barrier creams to protect skin from contact with the

N/A

material. Do not eat drink or smoke while working with the material. Always wash hands before smoking, eating, drinking or using the toilet and after finishing work. Observe the usual precautions when handling chemicals.

9. PHYSICAL AND CHEMICAL PROPERTIES:

Form : Liquid Color : colored

Odor : characteristic

Change in physical state : N/A
Boiling point, °C (mm Hg) : N/A

Melting point, °C

Flash Point (°C) : > 100 °C Auto ignition temperature (°C) : N/A Explosion limits : N/A

-lower -upper

Thermal decomposition :



Specific gravity (°C) : 1.4 (25)

Vapor pressure, mbar (°C) : < 1000mbar (50) Viscosity (°C) : 150 – 300 poise (25)

pH value (°C) : N/A Solubility in water (°C) : N/A

10. STABILITY AND REACTIVITY:

Chemical stability : Stable under normal storage and application

temperature

Incompatible materials : Strong acids, bases and oxidizing agents.

Hazardous decomposition Products : Carbon dioxide and phenolic produced under

combustion

11. TOXICOLOGICAL INFORMATION:

Health Hazard Summary : Susceptible individuals may develop allergic reactions

such as dermatitis or asthma like symptoms on a single significant skin exposure or may become sensitized to the material on repeated contact. Hence it is imperative

that all forms of exposure be kept to an absolute

minimum.

Inhalation:May cause irritation to nose and mucous membrane.Eyes:May cause eye irritation, redness and may be capable of

causing corneal scarring.

Ingestion : Only very slightly toxic.

12. ECOLOGICAL INFORMATION:

Ecology : Do not discharge into sewers unless connected to a

wastewater treatment plant.

13. DISPOSAL CONSIDERATIONS:

Disposal Method and Containers : Ensure containers are sealed. Dispose of to an approved

landfill site. Refer to Waste Management Authority.

Special Precautions (Landfill/Incineration): None Known



14. TRANSPORT INFORMATION:

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

15. REGULATORY INFORMATION:

Proposed classification : Xi, Irritant

N Dangerous for the environment.

Risk Phrase(s) : R36/38, Irritating to eyes and skin

: R43, May cause sensitization by skin contact

Safety Phrase(s) : S37/39, Wear suitable gloves and eye/face protection

S51, Use in a well-ventilated area

16. OTHER INFORMATION:

The data and advice given apply when the product is used for the stated application or applications. The product is not sold as suitable for any other applications. Use of the product for applications other than as stated in the sheet may give rise to risks not mentioned in this sheet. The product should not be used other than for the stated application or applications without seeking advice from MATEX.

If the product has been purchased for supply to a third party for use at work, it is the purchaser's duty to take all necessary steps to ensure that any person handling of using the product is provided with the information in this sheet.

It is the responsibility and duty of the employer to inform employees and others who may be affected of hazards described in this sheet and of any precautions which should be taken.

This sheet does not constitute or substitute for the users own assessment of workplace risk, as required by other health and safety legislation.

Further copies of this Safety Data Sheet may be obtained from MATEX.



NON HAZARDOUS – CHEMICAL IDENTIFICATION CODE NOT APPLICABLE

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY UNDERTAKING:

Product Name : COLORTEC POXY PART B

HS CODE : 39089000

Application : High performance epoxy grout for tiles - hardener

Manufacturer : MATEX CONSTRUCTION CHEMICALS

MANUFACTURING CO. L.L.C.

 Address
 : P.O. Box 29585

 Telephone
 : +971 4 3334140

 Fax
 : +971 4 3334115

 Email
 : info@matex.ae

Website : www.matex-global.com

2. HAZARDS IDENTIFICATION:

Hazardous identification : C (Corrosive)

Risk Phrases : R20/21/22, Harmful by inhalation, in contact with skin

and if swallowed

: R34, Causes burns

: R43, May cause sensitization by skin contact.

Safety Phrases : S26, In case of contact with eyes, rinse immediately

with plenty of water and seek medical advice.

: S36,27/39, Wear suitable protective clothing, gloves

and eye/face protection.

: S45, In case of accident or if you feel unwell, seek

medical advice immediately (show the label where

possible).

: S61, Avoid release to the environment. Refer to special

of as hazardous wastes.

3. COMPOSITION / INFORMATION ON INGREDIENTS:

Ingredients	% Composition	CAS No.
Epoxy hardener	100	68953-36-6



4. FIRST AID MEASURES:

Eyes : Remove contact lenses. Hold eyelids apart. Immediately

flush eyes with plenty of water for at least 15 minutes.

Get immediate medical attention.

Skin : Wash thoroughly with soap and water. Remove

contaminated clothing. Thoroughly wash clothing

before reuse. Render unusable and discard contaminated shoes and leather articles.

Inhalation : Remove to fresh air. Give artificial respiration. If

breathing is difficult, give oxygen. Get immediate

medical attention.

Ingestion : If conscious, drink large quantities of water. Induce

vomiting. Call a physician or poison control center immediately. NEVER give anything by mouth to an unconscious person. NEVER induce vomiting in an

unconscious person.

5. FIRE FIGHTING MEASURES:

Fire fighting procedures : Evacuate area immediately. Do not fight fire.

Extinguishing media : Deluge with large quantities of water as quickly as

possible by automatic sprinkles or fire hose from a

protected location.

Product is self-oxidizing.

Conditions to Avoid : Avoid impact, friction, heat, sparks, or flame.

Hazardous combustion : If heated to combustion, the following substances may

be products formed: carbon monoxide, carbon dioxide, nitrogen, water, hydrogen, nitrogen oxides, methane, aldehydes, carboxylic acid, and hydrogen cyanide.

6. ACCIDENTAL RELEASE MEASURES:

Clean up spills immediately using soft natural bristle brush and conductive rubber or conductive plastic shovel. Use caution, material is sensitive to initiation from sources such as heat, flame, shock, friction, or sparks. In case of accidental spill or release, refer to Section 8, Personal Protective Equipment and General Hygiene Practices.



7. HANDLING AND STORAGE:

General measures : Do not pressurize or expose containers to heat, flame,

sparks, static electricity, or other sources of ignition. Store in a cool, dry place, approximately 68°F (20°C). Store only in Department of Transportation approved containers. Check old product for deterioration

regularly.

Materials or conditions to avoid : Avoid storing product near incompatible materials. Do

not store near flammable materials. Do not keep deteriorated or salvaged product. Keep away from heat, flame, sparks, and other ignition sources. Do not store

in direct sunlight or expose to UV radiation.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION:

General Hygienic Practices : Avoid contact with eyes, skin and clothing. Avoid

breathing dust, vapor, or mist. Wash thoroughly after handling, and before eating, drinking, or smoking. Avoid contamination of food, beverages, or smoking materials. Remove contaminated clothing promptly and clean thoroughly before reuse. Discard contaminated leather

articles.

Recommended Exposure Limits:

Hazardous Component Wt. % Limit Basis

	TWA		STEL	
	ppm	mg/m³	ppm	mg/m³
1) ACGIH	N/E	N/E	N/E	N/E
2) ACGIH	N/E	N/E	N/E	N/E

Personal Protective Equipment : Safety glasses

: Impervious gloves

: Appropriate respiratory protection is required when

exposure to airborne contaminants may exceed

acceptable limits.



: Respirators should be selected and used in accordance

with OSHA, Subpart I (29 CFR 1910, 134) and

manufacturer's recommendations.

: Flame retardant clothing.

: Wear conductive safety shoes.

Work Practices and Engineering Controls: Do NOT smoke in areas where powder is stored or used.

: Material is shock sensitive. Use care in handling.

: Keep away from ignition sources. Friction can cause

ignition.

: Eye wash fountains and safety showers should be easily

accessible.

: Prevent build-up of static electric charges.

: Use process enclosures, local exhaust ventilation, or

other engineering controls to control airborne levels

below recommended exposure limits.

Protective Measures during Repair and Maintenance:

: Eliminate ignition sources and prevent build-up of static

electric charges.

: Use spark-proof tools and explosion-proof equipment.

: Wetting work area with water will greatly reduce

hazards.

: Completely remove product from area, and thoroughly

clean all equipment, piping, or vessels before beginning

maintenance or repairs.

: A work permit system is recommended for any

preparation and clean-up.

9. PHYSICAL AND CHEMICAL PROPERTIES:

Form : Liquid

Colour : Light yellow Odour : characteristic

Change in physical state : N/A
Boiling point, °C (mm Hg) : > 150°C

Melting point, °C

Flash Point (°C) : > 70°C
Auto ignition Temperature : N/A



-lower -upper

Thermal decomposition : N/A

Specific gravity (°C) : 0.95 - 1.05 (25)

Vapour pressure, mbar (°C) : N/A

Viscosity (°C) : 0.5 - 1.5 poise (25)

pH value (°C)

Solubility in water (°C) : N/A

Further information

10. STABILITY AND REACTIVITY:

General stability considerations : Stable under recommended handling and storage

conditions.

Incompatible materials : Incompatible with: acids, oxidizing agents, alkalis and

amines and strong sunlight or ultraviolet light.

Hazardous decomposition : None anticipated under normal or recommended

handling and products storage conditions.

Hazardous polymerization : Not anticipated under normal or recommended

handling and storage conditions.

11. TOXICOLOGICAL INFORMATION:

Reported human effects : No human toxicity studies have been carried out with

this product.

Reported animal effects

Acute Toxicity : oral (rat) LD50 1300 mg/kg (calculated)

inhalation (rat) LC50 not determinedskin (rabbit)) LD50 not determined

Skin irritation:May cause irritation to skinEye irritation:May cause irritation to eyes

Chronic toxicity : No information

Sensitizing:May cause sensitization by skin contactCarcinogenicity information:IARC : Group 4ACHIH : A5

Reproductive effects : No studies on reproductive effects have been carried out

with this product.

Mutagenicity / genotoxicity Information: No mutagenicity studies have been carried out with this

product.



12. ECOLOGICAL INFORMATION:

Ecotoxicity : No ecological studies have been carried out with this

product.

13. DISPOSAL CONSIDERATIONS:

Waste Disposal Methods: Disposal of waste and resin should be carried out under

the direct supervision of a qualified person. For

industrial disposal, federal hazardous waste regulations allow open burning of wastes in permitted facilities.
Burn in the open in an isolated location in small, shallow piles not over one inch deep. Stay upwind. Do not

breathe products of combustion. State or local regulations may be more stringent than federal

regulations.

For disposal of small quantities, contact state or local environmental agencies for options.

14. TRANSPORT INFORMATION:

UN Haz. Class : 8 UN Number : 1760 Packaging Group : 3

15. REGULATORY INFORMATION:

Hazardous identification : C (Corrosive)

Risk Phrases : R20/21/22, Harmful by inhalation, in contact with skin

and if swallowed R34, Causes burns

: R43, May cause sensitization by skin contact.

Safety Phrases : S26, In case of contact with eyes, rinse immediately

with plenty of water and seek medical advice.

S36, 27/39, Wear suitable protective clothing, gloves

and eye/face protection.

S45, In case of accident or if you feel unwell, seek

medical advice immediately (show the label where

possible).



S61, Avoid release to the environment. Refer to special of as hazardous wastes.

16. OTHER INFORMATION:

The data and advice given apply when the product is used for the stated application or applications. The product is not sold as suitable for any other applications. Use of the product for applications other than as stated in the sheet may give rise to risks not mentioned in this sheet. The product should not be used other than for the stated application or applications without seeking advice from MATEX.

If the product has been purchased for supply to a third party for use at work, it is the purchaser's duty to take all necessary steps to ensure that any person handling of using the product is provided with the information in this sheet.

It is the responsibility and duty of the employer to inform employees and others who may be affected of hazards described in this sheet and of any precautions which should be taken.

This sheet does not constitute or substitute for the users own assessment of workplace risk, as required by other health and safety legislation.

Further copies of this Safety Data Sheet may be obtained from MATEX.

MATEX Rev-00-1015