

NON HAZARDOUS - CHEMICAL IDENTIFICATION CODE NOT APPLICABLE

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY UNDERTAKING:

Product Name : EPOFIX FX PART A

HS CODE : 39095000

Application:Epoxy Polyurethane Flowable AdhesiveManufacturer:MATEX CONSTRUCTION CHEMICALS

MANUFACTURING CO. L.L.C.

 Address
 :
 P.O. Box 29585

 Telephone
 :
 +971 4 3334140

 Fax
 :
 +971 4 3334115

 Email
 :
 info@matex.ae

Website : www.matex-global.com

2. HAZARDS IDENTIFICATION:

Hazard Designation : Xi Irritant

Risk Phrase(s) : R36/38, Irritating to eyes and skin

R43, May cause sensitization by skin contact

Safety Phrase(s) : S37/39, Wear suitable gloves and eye/face protection

: S51, Use in a well-ventilated area

3. COMPOSITION / INFORMATION ON INGREDIENTS:

| INGREDIENTS: | | | | | |
|--------------------|---------------|-------------|--|--|--|
| Name | % Composition | CAS No. | | | |
| Liquid Epoxy | 15-30 | 25068-38-6 | | | |
| Blocked Isocyanate | 35-55 | Proprietary | | | |
| Calcium Carbonate | 15-25 | 471-34-1 | | | |
| Additives | <2.0 | proprietary | | | |



4. FIRST AID MEASURES:

Skin contact : Flush with large amounts of clean water, use soap if

available. Remove any contaminated clothing.

Eye contact : Check for and remove any contact lenses. Flush with

large amounts of clean warm water for 15 minutes. Get

Prompt medical attention.

Inhalation : Immediately move victim to fresh air. If breathing has

stopped then administer artificial respiration. Get

prompt medical attention.

Ingestion : Not a normal route of injury. Do not induce vomiting;

give large quantities of water, get immediate medical attention. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquids into lungs. Do not give anything by mouth to an unconscious

person.

5. FIRE FIGHTING MEASURES:

Hazardous combustion

Products : Oxides of Carbon and other possible toxic fumes from

fire

Firefighting measures : Foam, carbon dioxide, dry chemical. Wear protective

equipment including self-contained apparatus.

6. ACCIDENTAL RELEASE MEASURES:

Method and Materials for

Clean Up : Spill should be contained by bundling and absorbing with

dry inert filler (e.g. vermiculite, sand, oil etc), which can

be shoveled into appropriately labeled drums. Disposal should be affected by approved waste

disposal organization according to local regulations.

Environmental Precautions : Avoid subsoil penetration. Do not allow to enter into

drains, sewers or waterways.



7. HANDLING AND STORAGE:

Precautions for Safe Handling : Wear personal protective equipment (PPE) as per

Section 8

Conditions for Safe Storage : Keep containers tightly closed; store under cool dry

conditions. Keep away from food and drink. Keep out of reach of children. Store under cover and away from direct sunlight and moisture. Store at 5°C to 35°C. Keep

away from incompatible materials.

8. EXPOSURE CONTROLS / PERSONAL PROTECTIONS:

Engineering Controls : Ventilation is recommended under normal use

Conditions. State regulations on speed and direction of Airflow away from operators must be observed. Keep

containers closed when not in use.

Exposure Standards : None established for this product.

Personal Protective Equipment (PPE):

Respiratory protection : Type A1 if ventilation is inadequate

Glove type (AS2161) : Chemical resistant, impervious gloves e.g. PVC, butyl

rubber or nitrile rubber gauntlets (consult your local

glove supplier / manufacturer).

Eye Protection : Chemical worker's goggles or well-fitting safety glasses

Or full face shield

Clothing : No special clothing required but overalls or other

suitable industrial clothing which provides full skin coverage are suggested as a general precaution,

especially where heavy contamination is likely.

Other : Use barrier creams to protect skin from contact with the

material. Do not eat drink or smoke while working with the material. Always wash hands before smoking, eating, drinking or using the toilet and after finishing work. Observe the usual precautions when handling chemicals.



9. PHYSICAL AND CHEMICAL PROPERTIES:

Form liquid Change in physical state N/A Boiling point, °C (mm Hg) N/A Melting point (°C) N/A Flash point (°C) N/A Autoignition temperature (°C) N/A Thermal decomposition N/A Density, g/cm3 (°C) 1.25 Vapour pressure, mbar (°C) N/A Viscosity (°C) N/A pH value (°C) N/A Solubility in water (°C) N/A

10. STABILITY AND REACTIVITY:

Chemical stability Stable under normal storage and application temperature

Incompatible materials Strong acids, bases and oxidizing agents.

Hazardous decomposition

Products Oxides of carbon and other possibly toxic fumes from fire.

Hazardous reactions Hazardous polymerization will not occur.

11. TOXICOLOGICAL INFORMATION:

Health Hazard Summary Susceptible individuals may develop allergic

reactions such as dermatitis or asthma like

symptoms on a single significant skin exposure or may become sensitized to the material on repeated contact. Hence it is imperative that all forms of exposure be kept to an absolute

minimum.

Inhalation May cause irritation to nose and mucous membrane. Eyes

May cause eye irritation, redness and may be capable of

causing corneal scarring.

Ingestion Only very slightly toxic.



12. ECOLOGICAL INFORMATION:

Ecology : Do not discharge into sewers unless connected to

a wastewater treatment plant.

13. DISPOSAL CONSIDERATIONS:

Disposal Method and

Containers : Ensure containers are sealed. Dispose of to an approved

land fill site. Refer to Waste Management Authority.

Special Precautions

(Landfill / Incineration) : None Known

14. TRANSPORT INFORMATION:

CFR_ROAD : NOT REGULATED FOR TRANSPORT IATA_C : NOT REGULATED FOR TRANSPORT IMDG : NOT REGULATED FOR TRANSPORT CFR_RAIL : NOT REGULATED FOR TRANSPORT

15. REGULATORY INFORMATION:

Proposed classification: Xi, Irritant

N Dangerous for the environment.

Risk phrase(s) : R36/38, Irritating to eyes and skin

R43, May cause sensitization by skincontact

R51/53, Toxic to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.

Safety phrase(s) : S28, After contact with skin, wash immediately with

plenty of water.

S37, Wear suitable glover and eyes/face protection

S61, Avoid release to the environment.



16. OTHER INFORMATION:

The data and advice given apply when the product is used for the stated application or applications. The product is not sold as suitable for any other applications. Use of the product for applications other than as stated in the sheet may give rise to risks not mentioned in this sheet. The product should not be used other than for the stated application or applications without seeking advice from MATEX.

If the product has been purchased for supply to a third party for use at work, it is the purchaser's duty to take all necessary steps to ensure that any person handling of using the product is provided with the information in this sheet.

It is the responsibility and duty of the employer to inform employees and others who may be affected of hazards described in this sheet and of any precautions which should be taken.

This sheet does not constitute or substitute for the users own assessment of workplace risk, as required by other health and safety legislation.

Further copies of this safety Data Sheet may be obtained from MATEX.

MATEX Rev-00-1023



NON HAZARDOUS - CHEMICAL IDENTIFICATION CODE NOT APPLICABLE

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY UNDERTAKING:

Product Name : EPOFIX FX PART B

HS CODE : 39095000

Application:Epoxy Polyurethane Flowable AdhesiveManufacturer:MATEX CONSTRUCTION CHEMICALS

MANUFACTURING CO. L.L.C.

 Address
 :
 P.O. Box 29585

 Telephone
 :
 +971 4 3334140

 Fax
 :
 +971 4 3334115

 Email
 :
 info@matex.ae

Website : www.matex-global.com

2. HAZARDS IDENTIFICATION:

Hazard Designation : C (Corrosive)

Risk Phrases : R20/21/22, Harmful by inhalation, in contact with skin and

if swallowed

: R34, Causes burns

: R43, May cause sensitization by skin contact

3. COMPOSITION / INFORMATION ON INGREDIENTS:

| INGREDIENTS: | | | | | |
|--------------------------|---------------|-------------|--|--|--|
| Name | % Composition | CAS No. | | | |
| Modified Aliphatic Amine | >90 | proprietary | | | |

4. FIRST AID MEASURES:

Eyes : Remove contact lenses. Hold eyelids apart. Immediately

flush eyes with plenty of water for at least 15 minutes.

Get immediate medical attention.



Skin : Wash thoroughly with soap and water. Remove contaminated

clothing. Thoroughly wash clothing before reuse. Render unusable

and discard contaminated shoes and leather articles.

Inhalation : Remove to fresh air. Give artificial respiration. If breathing is difficult

give oxygen. Get immediate medical attention

Ingestion : If conscious, drink large quantities of water. Induce vomiting

Call a physician or poison control center immediately NEVER give anything by mouth to an unconscious person

NEVER induce vomiting in an unconscious person

5. FIRE FIGHTING MEASURES:

Fire fighting procedures : Evacuate area immediately. Do not fight fire.

Extinguishing media : Deluge with large quantities of water as quickly as

possible by automatic sprinkles or fire hose from a

protected location.

Product is self-oxidizing.

Conditions to Avoid : Avoid impact, friction, heat, sparks, or flame.

Hazardous combustion : If heated to combustion, the following substances may

be products formed: carbon monoxide, carbon dioxide, Nitrogen, water, hydrogen, nitrogen oxides, methane,

Aldehydes, carboxylic acid, and hydrogen cyanide

6. ACCIDENTAL RELEASE MEASURES:

Clean up spills immediately using soft natural bristle brush and conductive rubber or conductive plastic shovel. Use caution, material is sensitive to initiation from sources such as heat, flame, shock, friction, or sparks. In case of accidental spill or release, refer to Section 8, Personal Protective Equipment and General Hygiene Practices.

7. HANDLING AND STORAGE:

General measures : Do not pressurize or expose containers to heat, flame, sparks,

static electricity, or other sources of ignition. Store in a cool, dry place, approximately 68°F (20°C). Store only in Department of

Transportation approved containers.

Check old product for deterioration regularly.



Materials or conditions to avoid: Avoid storing product near incompatible materials. Do not store near flammable materials. Do not keep deteriorated or salvaged product. Keep away from heat, flame, sparks, and other ignition sources. Do not store in direct sunlight or expose to UV radiation.

8. EXPOSURE CONTROLS / PERSONAL PROTECTIONS:

General Hygienic Practices : Avoid contact with eyes, skin and clothing. Avoid

breathing dust, vapor, or mist. Wash thoroughly after handling, and before eating, drinking, or smoking. Avoid contamination of food, beverages, or smoking materials. Remove contaminated clothing promptly and clean thoroughly before reuse. Discard contaminated

leather articles.

Recommended Exposure Limits:

Hazardous Component Wt. % Limit Basis

| | TWA | | STEL | |
|----------|-----|-------|------|-------|
| | ppm | mg/m³ | ppm | mg/m³ |
| 1) ACGIH | N/E | N/E | N/E | N/E |
| 2) ACGIH | N/E | N/E | N/E | N/E |

Personal Protective Equipment:

Safety glasses

Impervious gloves

Appropriate respiratory protection is required when exposure to airborne contaminants may exceed acceptable limits.

Respirators should be selected and used in accordance with OSHA, Subpart I (29 CFR 1910, 134) and manufacturers recommendations.

Flame retardant clothing.

Wear conductive safety shoes.

Work Practices and Engineering Controls:

Do NOT smoke in areas where powder is stored or used.

Material is shock sensitive. Use care in handling.

Keep away from ignition sources. Friction can cause ignition.



Eye wash fountains and safety showers should be easily accessible.

Prevent build-up of static electric charges.

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Protective Measures During Repair and Maintenance:

Eliminate ignition sources and prevent build-up of static electric charges.

Use spark-proof tools and explosion-proof equipment.

Wetting work area with water will greatly reduce hazards.

Completely remove product from area, and thoroughly clean all equipment, piping, or vessels before beginning maintenance or repairs.

A work permit system is recommended for any preparation and clean-up.

9. PHYSICAL AND CHEMICAL PROPERTIES:

Form liquid Change in physical state N/A Boiling point, °C (mm Hg) N/A Melting point (°C) N/A N/A Flash point (°C) Autoignition temperature (°C) N/A Thermal decomposition N/A Density, g/cm3 (°C) 1.03 Vapour pressure, mbar (°C) N/A Viscosity (°C) N/A pH value (°C) N/A Solubility in water (°C) N/A

10. STABILITY AND REACTIVITY:

General stability considerations: Stable under recommended handling and storage conditions.

Incompatible materials : Incompatible with: acids, oxidizing agents, alkalis and

amines and strong sunlight or ultraviolet light.

Hazardous decomposition : None anticipated under normal or recommended

handling and products storage conditions.



Hazardous polymerization : Not anticipated under normal or recommended handling

and storage conditions.

11. TOXICOLOGICAL INFORMATION:

Reported human effects : No human toxicity studies have been carried out with this

product.

Reported animal effects :

Acute Toxicity oral (rat) LD₅₀ 1300 mg/kg (calculated)

inhalation (rat) LC₅₀ not determined skin (rabbit)) LD₅₀ not determined

Skin irritation : May cause irritation to skin Eye irritation : May cause irritation to eyes

Chronic toxicity : No information

Sensitizing : May cause sensitization by skin contact Carcinogenicity informatio : IARC : Group 4 ACHIH : A5

Reproductive effects : No studies on reproductive effects have been carried out

with this product.

Mutagenicity / genotoxicity : No mutagenicity studies have been carried out with this

Information product

12. ECOLOGICAL INFORMATION:

Ecotoxicity : No ecological studies have been carried out with this product

13. DISPOSAL CONSIDERATIONS:

Waste Disposal Methods:

Disposal of waste and resin should be carried out under the direct supervision of a qualified person. For industrial disposal, federal hazardous waste regulations allow open burning of wastes in permitted facilities. Burn in the open in an isolated location in small, shallow piles not over one inch deep. Stay upwind. Do not breathe products of combustion. State or local regulations may be more stringent than federal regulations.

For disposal of small quantities, contact state or local environmental agencies for options.



14. TRANSPORT INFORMATION:

RID/ADR :

UN Haz. Class : 8 UN No. : 1760

IMDG Code :

GGVE/GGVS :

ICAO/IATA : Class 3.3 Packing Group III

ADNR :

Other Information : Environmentally hazardous substance

15. REGULATORY INFORMATION:

Labeling according to EEC Directives

Hazardous identification : C (Corrosive)

Harmful by inhalation in contact with skin and if swallowed (R20/21/22). Causes burns (R34). May cause sensitization by skin contact (R43).

In case of contact with eyes, rinse immediately with plenty of water and seek medical advise (26)

Wear suitable protective clothing, gloves and eye/face protection (S36/37/39). In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible) (S45).

Avoid release to the environment. Refer to special instructions / safety data sheets (S61)



16. OTHER INFORMATION:

The data and advice given apply when the product is used for the stated application or applications. The product is not sold as suitable for any other applications. Use of the product for applications other than as stated in the sheet may give rise to risks not mentioned in this sheet. The product should not be used other than for the stated application or applications without seeking advice from MATEX.

If the product has been purchased for supply to a third party for use at work, it is the purchaser's duty to take all necessary steps to ensure that any person handling of using the product is provided with the information in this sheet.

It is the responsibility and duty of the employer to inform employees and others who may be affected of hazards described in this sheet and of any precautions which should be taken.

This sheet does not constitute or substitute for the users own assessment of workplace risk, as required by other health and safety legislation.

Further copies of this safety Data Sheet may be obtained from MATEX.

MATEX Rev-00-1023