

NON HAZARDOUS – CHEMICAL IDENTIFICATION CODE NOT APPLICABLE

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY UNDERTAKING:

Product Name : HYDROPOXY DWT Part A

H.S. Code : 32089000

Application : Solvent Free Epoxy Waterproofing for Potable Water Tanks

Manufacturer : MATEX CONSTRUCTION CHEMICALS

MANUFACTURING CO. L.L.C.

 Address
 :
 P.O. Box 29585

 Telephone
 :
 +971 4 3334140

 Fax
 :
 +971 4 3334115

 Email
 :
 info@matex.ae

Website : www.matex-global.com

2. HAZARDS IDENTIFICATION:

Hazard Designation : Xi Irritant

Risk Phrase(s) : R36/38, Irritating to eyes and skin

R43, May cause sensitization by skin contact

Safety Phrase(s) : S37/39, Wear suitable gloves and eye/face protection

: S51, Use in a well-ventilated area

3. COMPOSITION / INFORMATION ON INGREDIENTS:

Ingredients	% Composition	CAS No.
Epoxy resin	40-60	25068-38-6
Titanium Dioxide	8-15	13463-67-7
Barium Sulphate	35-50	7727-43-7

4. FIRST AID MEASURES:

Skin contact : Flush with large amounts of clean water, use soap if available.

Remove any contaminated clothing.

Eye contact: Check for and remove any contact lenses. Flush with large

amounts of clean warm water for 15 minutes.

Get prompt medical attention.

Inhalation : Immediately move victim to fresh air. If breathing has



stopped then administer artificial respiration. Get prompt

medical attention.

Ingestion : Not a normal route of injury. Do not induce vomiting;

give large quantities of water, get immediate medical

attention. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquids into lungs. Do not give

anything by mouth to an unconscious person.

5. FIRE FIGHTING MEASURES:

Hazardous combustion

Products : Oxides of Carbon and other possible toxic fumes from fire

Firefighting measures : Foam, carbon dioxide, dry chemical. Wear protective equipment

including self-contained apparatus.

6. ACCIDENTAL RELEASE MEASURES:

Method and Materials for

Clean Up : Spill should be contained by bundling and absorbing with dry

inert filler (e.g. vermiculite, sand, oil etc), which can be shoveled into appropriately labeled drums. Disposal should be effected by

approved waste disposal organization according to local

regulations.

Environmental Precautions: Avoid subsoil penetration. Do not allow to enter into drains,

sewers or waterways.

7. HANDLING AND STORAGE:

Precautions for Safe Handling: Wear personal protective equipment (PPE) as per Section

Conditions for Safe Storage : Keep containers tightly closed; store under cool dry conditions.

Keep away from food and drink. Keep out of reach of children. Store under cover and away from direct sunlight and moisture. Store at 5°C to 35°C. Keep away from incompatible materials.



8. EXPOSURE CONTROLS / PERSONAL PROTECTION:

Engineering Controls : Ventilation is recommended under normal use conditions. State

regulations on speed and direction of airflow away from

operators must be observed. Keep containers closed when not in

use.

Exposure Standards : None established for this product.

Personal Protective Equipment (PPE):

Respiratory protection : Type A1 if ventilation is inadequate

Glove type (AS2161) : Chemical resistant, impervious gloves e.g. PVC, butyl rubber or

nitrile rubber gauntlets (consult your local glove supplier /

manufacturer).

Eye Protection : Chemical worker's goggles or well-fitting safety glasses or full

face shield.

Clothing : No special clothing required but overalls or other suitable

industrial clothing which provides full skin coverage are suggested as a general precaution, especially where heavy

contamination is likely.

Other : Use barrier creams to protect skin from contact with the

material. Do not eat drink or smoke while working with the material. Always wash hands before smoking, eating, drinking or using the toilet and after finishing work. Observe the usual

precautions when handling chemicals.

9. PHYSICAL AND CHEMICAL PROPERTIES:

Form : Liquid
Colour : Various
Odour : characteristic
Change in physical state : N/A

Boiling point, °C(mm Hg) : N/A

Melting point, °C

Flash Point (°C) : > 100 °C
Autoignition temperature (°C) : N/A
Explosion limits : N/A

-lower -upper

Thermal decomposition : N/A
Specific gravity (°C) : 1.7 (25)



Vapour pressure, mbar (°C) : < 1000mbar (50) **Viscosity (°C)** : 150 – 300 poise (25)

pH value (°C) : N/A Solubility in water (°C) : N/A

10. STABILITY AND REACTIVITY:

Chemical stability : Stable under normal storage and application temperature

Incompatible materials : Strong acids, bases and oxidizing agents.

Hazardous decomposition : Oxides of carbon and other possibly toxic fumes from fire.

Products

Hazardous reactions : Hazardous polymerization will not occur.

11. TOXICOLOGICAL INFORMATION:

Health Hazard Summary : Susceptible individuals may develop allergic reactions such as

dermatitis or asthma like symptoms on a single significant skin exposure or may become sensitized to the material on repeated contact. Hence it is imperative that all forms of exposure be kept

to an absolute minimum.

Inhalation : May cause irritation to nose and mucous membrane.

Eyes : May cause eye irritation, redness and may be capable of causing

corneal scarring.

Ingestion : Only very slightly toxic.

12. ECOLOGICAL INFORMATION:

Ecology : Do not discharge into sewers unless connected to a wastewater

treatment plant.

13. DISPOSAL CONSIDERATIONS:

Disposal Method and

Containers

Special Precautions (Landfill / Incineration)

: None Known

: Ensure containers are sealed. Dispose of to an approved landfill

site. Refer to Waste Management Authority.



14. TRANSPORT INFORMATION:

CFR_ROAD : NOT REGULATED FOR TRANSPORT IATA_C : NOT REGULATED FOR TRANSPORT IMDG : NOT REGULATED FOR TRANSPORT CFR_RAIL : NOT REGULATED FOR TRANSPORT

15. REGULATORY INFORMATION:

Proposed classification : Xi, Irritant

N Dangerous for the environment.

Risk phrase(s) : R36/38, Irritating to eyes and skin

R43, May cause sensitization by skincontact

R51/53, Toxic to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.

Safety phrase(s) : S28, After contact with skin, wash immediately with plenty of

water.

S37, Wear suitable glover and eyes/face protection

: S61, Avoid release to the environment.

16. OTHER INFORMATION:

The data and advice given apply when the product is used for the stated application or applications. The product is not sold as suitable for any other applications. Use of the product for applications other than as stated in the sheet may give rise to risks not mentioned in this sheet. The product should not be used other than for the stated application or applications without seeking advice from MATEX.

If the product has been purchased for supply to a third party for use at work, it is the purchaser's duty to take all necessary steps to ensure that any person handling of using the product is provided with the information in this sheet.

It is the responsibility and duty of the employer to inform employees and others who may be affected of hazards described in this sheet and of any precautions which should be taken.

This sheet does not constitute or substitute for the users own assessment of workplace risk, as required by other health and safety legislation.

Further copies of this Safety Data Sheet may be obtained from MATEX.



NON HAZARDOUS – CHEMICAL IDENTIFICATION CODE NOT APPLICABLE

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY UNDERTAKING:

Product Name : HYDROPOXY DWT Part B

H.S. Code : 32089000

Application : Solvent Free Epoxy Waterproofing for Potable Water Tanks

Manufacturer : MATEX CONSTRUCTION CHEMICALS

MANUFACTURING CO. L.L.C.

 Address
 :
 P.O. Box 29585

 Telephone
 :
 +971 4 3334140

 Fax
 :
 +971 4 3334115

 Email
 :
 info@matex.ae

Website : www.matex-global.com

2. HAZARDS IDENTIFICATION:

Hazardous identification : C (Corrosive)

Harmful by inhalation, in contact with skin and if swallowed (R20/21/22).

Causes burns (R34)

May cause sensitization by skin contact (R43).

3. COMPOSITION / INFORMATION ON INGREDIENTS:

Ingredients	% Composition	CAS No.	
Curing Agent	100	68410-23-1	

4. FIRST AID MEASURES:

Eyes : Remove contact lenses. Hold eyelids apart. Immediately flush

eyes with plenty of water for at least 15 minutes.

Get immediate medical attention.

Skin : Wash thoroughly with soap and water. Remove contaminated

clothing. Thoroughly wash clothing before reuse. Render

unusable and discard contaminated shoes and leather articles.

Inhalation: Remove to fresh air. Give artificial respiration. If breathing is



difficult, give oxygen. Get immediate medical attention. **Ingestion**

If conscious, drink large quantities of water. Induce vomiting.

Call a physician or poison control center immediately. NEVER give anything by mouth to an unconscious person.

NEVER induce vomiting in an unconscious person.

5. FIRE FIGHTING MEASURES:

Fire fighting procedures Evacuate area immediately. Do not fight fire.

Extinguishing media Deluge with large quantities of water as quickly as possible by

automatic sprinkles or fire hose from a protected location.

Product is self-oxidizing.

Conditions to Avoid Avoid impact, friction, heat, sparks, or flame.

Hazardous combustion If heated to combustion, the following substances may be

> formed: carbon monoxide, carbon dioxide, nitrogen, water, hydrogen, nitrogen oxides, methane, aldehydes, carboxylic

acid, and hydrogen cyanide.

6. ACCIDENTAL RELEASE MEASURES:

products

Clean up spills immediately using soft natural bristle brush and conductive rubber or conductive plastic shovel. Use caution, material is sensitive to initiation from sources such as heat, flame, shock, friction, or sparks. In case of accidental spill or release, refer to Section 8, Personal Protective Equipment and General Hygiene Practices.

7. HANDLING AND STORAGE:

Do not pressurize or expose containers to heat, flame, sparks, General measures

> static electricity, or other sources of ignition. Store in a cool, dry place, approximately 68°F (20°C). Store only in Department of

Transportation approved containers.

Check old product for deterioration regularly.

Materials or conditions to avoid: Avoid storing product near incompatible materials. See section

> 10. Do not store near flammable materials. Do not keep deteriorated or salvaged product. Keep away from heat, flame,

sparks, and other ignition sources.

Do not store in direct sunlight or expose to UV radiation.



8. EXPOSURE CONTROLS / PERSONAL PROTECTION:

General Hygienic Practices : Avoid contact with eyes, skin and clothing. Avoid breathing dust,

vapor, or mist. Wash thoroughly after handling, and before eating, drinking, or smoking. Avoid contamination of food, beverages, or smoking materials. Remove contaminated clothing

promptly and clean thoroughly before reuse. Discard

contaminated leather articles.

Recommended Exposure Limits:

Hazardous Component Wt. % Limit Basis

	TWA		STEL	
	ppm	mg/m³	ppm	mg/m³
1) ACGIH	N/E	N/E	N/E	N/E
2) ACGIH	N/E	N/E	N/E	N/E

Personal Protective Equipment:

Safety glasses

Impervious gloves

Appropriate respiratory protection is required when exposure to airborne contaminants may exceed acceptable limits.

Respirators should be selected and used in accordance with OSHA, Subpart I (29 CFR 1910, 134) and manufacturers recommendations.

Flame retardant clothing.

Wear conductive safety shoes.

Work Practices and Engineering Controls:

Do NOT smoke in areas where powder is stored or used.

Material is shock sensitive. Use care in handling.

Keep away from ignition sources. Friction can cause ignition.

Eye wash fountains and safety showers should be easily accessible.

Prevent build-up of static electric charges.

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Protective Measures During Repair and Maintenance:

Eliminate ignition sources and prevent build-up of static electric charges.



Use spark-proof tools and explosion-proof equipment.

Wetting work area with water will greatly reduce hazards.

Completely remove product from area, and thoroughly clean all equipment, piping, or vessels before beginning maintenance or repairs.

A work permit system is recommended for any preparation and clean-up.

9. PHYSICAL AND CHEMICAL PROPERTIES:

Form : Liquid
Colour : Light yellow
Odour : characteristic

Change in physical state : N/A Boiling point, $^{\circ}$ C(mm Hg) : > 200 $^{\circ}$ C

Melting point, °C

Flash Point(°C) : 105°C Autoignition Temperature : N/A

-lower -upper

Thermal decomposition : N/A

Specific gravity (°C) : 0.95 – 1.05 (25)

Vapour pressure, pa(°C) : 6.7 (20)

Viscosity(°C) : 150-300 MPa (25)

pH value(°C)

Solubility in water(°C) : N/A

Further information

10. STABILITY AND REACTIVITY:

General stability considerations: Stable under recommended handling and storage conditions. **Incompatible materials**: Incompatible with: acids, oxidizing agents, alkalis and amines

and strong sunlight or ultraviolet light.

Hazardous decomposition : None anticipated under normal or recommended handling and

products storage conditions.

Hazardous polymerization : Not anticipated under normal or recommended handling and

storage conditions.



11. TOXICOLOGICAL INFORMATION:

Reported human effects: No human toxicity studies have been carried out with this

product.

Reported animal effects

Acute Toxicity oral (rat) LD_{50} > 2000 mg/kg (calculated)

inhalation (rat) LC₅₀ not determined skin (rabbit)) LD₅₀ not determined

Skin irritation:May cause irritation to skinEye irritation:May cause irritation to eyes

Chronic toxicity : No information

Sensitizing : May cause sensitization by skin contact

Reproductive effects: No studies on reproductive effects have been carried out with

this product.

Mutagenicity / genotoxicity

information

No mutagenicity studies have been carried out with this

product.

12. ECOLOGICAL INFORMATION:

Ecotoxicity : Avoid subsoil penetration. Prevent product from entering drains.

Do not contaminate surface water.

13. DISPOSAL CONSIDERATIONS:

Waste Disposal Methods:

Disposal of waste and resin should be carried out under the direct supervision of a qualified person. For industrial disposal, federal hazardous waste regulations allow open burning of wastes in permitted facilities. Burn in the open in an isolated location in small, shallow piles not over one inch deep. Stay upwind. Do not breathe products of combustion. State or local regulations may be more stringent than federal regulations.

For disposal of small quantities, contact state or local environmental agencies for options.

14. TRANSPORT INFORMATION:

UN Haz. Class : 8 UN Number : 2289 Packaging Group : 3



15. REGULATORY INFORMATION:

Labeling according to EEC Directives

Hazardous identification : C (Corrosive)

Harmful by inhalation in contact with skin and if swallowed (R20/21/22). Causes burns (R34).

May cause sensitization by skin contact (R43).

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice (S26).

Wear suitable protective clothing, gloves and eye/face protection (S36/37/39). In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible) (S45).

Avoid release to the environment. Refer to special instructions / safety data sheets (S61)

16. OTHER INFORMATION:

The data and advice given apply when the product is used for the stated application or applications. The product is not sold as suitable for any other applications. Use of the product for applications other than as stated in the sheet may give rise to risks not mentioned in this sheet. The product should not be used other than for the stated application or applications without seeking advice from MATEX.

If the product has been purchased for supply to a third party for use at work, it is the purchaser's duty to take all necessary steps to ensure that any person handling of using the product is provided with the information in this sheet.

It is the responsibility and duty of the employer to inform employees and others who may be affected of hazards described in this sheet and of any precautions which should be taken.

This sheet does not constitute or substitute for the users own assessment of workplace risk, as required by other health and safety legislation.

Further copies of this Safety Data Sheet may be obtained from MATEX.