

#### NON HAZARDOUS – CHEMICAL IDENTIFICATION CODE NOT APPLICABLE

### 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY UNDERTAKING:

Product Name : HYDROTHANE WP2 PLUS, PART A

HS Code : 32089000

**Application** : Elastomeric Two Part Cold Applied Polyurea

Waterproofing Membrane

Manufacturer : MATEX CONSTRUCTION CHEMICALS

MANUFACTURING CO. L.L.C.

 Address
 :
 P.O. Box 29585

 Telephone
 :
 +971 4 3334140

 Fax
 :
 +971 4 3334115

 Email
 :
 info@matex.ae

Website : www.matex-global.com

#### 2. HAZARDS IDENTIFICATION:

Classification of the substance or mixture Classification (Regulation EC no. 1272/2008

Acute Tox. (oral)4: H302: Harmful if swallowed

Eye irritation, cat. 2 H319: Causes serious eye irritation

Skin sensitisation, cat. 1 H317: May cause an allergic skin reaction

Specific target organ toxicity

Repeated exposure, cat. 2 H373: May cause damage to organs through prolonged

or repeated exposure

Long-term (chronic) aquatic

Hazard, cat. 2 H411: Toxic to aquatic life with long lasting effects

Label Elements: The product is classified and required to be labelled in accordance with EC-directives Labelling according to Regulation (EC) 1272/2008

Hazard Pictograms







Signal Word Warning

Hazard Statements H302 Harmful if swallowed

H319 Causes serious eye irritation

H317 May cause an allergic skin reaction

H373 May cause damage to organs through prolonged or repeated exposure



H411 Toxic to aquatic life with long lasting effects

## **Precautionary Statements**

#### **Prevention:**

P260 Do not breathe vapours/spray

P264 Wash skin thoroughly after handling

P270 Do not eat, drink or smoke when using this product

P273 Avoid release to the environment

P280 Wear protective gloves/eye protection/face protection

### Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth

P302 + P352 IF ON SKIN: Wash with plenty of soap and water

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P314 Get medical advice/attention if you feel unwell

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention

P337 + P313 If skin irritation or rash occurs: Get medical advice/attention

P363 Wash contaminated clothing before reuse

P391 Collect spillage

### Disposal:

P501 Dispose of contents/container to an approved waste disposal plant

Other Hazards Further hazards were not determined with the current level of Knowledge

### 3. COMPOSITION / INFORMATION ON INGREDIENTS:

The product is a mixture.

INGREDIENTS:			
Name	% Composition	CAS No.	
Diethylmethylbenzenediamine	40 – 60	68479-98-1	
Filler	20 – 40	99439-28-8	
Titanium Dioxide	5 – 10	13463-67-7	
Additives	1-5	proprietary	



#### 4. FIRST AID MEASURES:

Most Important Symptom(s) Effect(s)

**Symptoms** : Allergic reactions

Excessive lachrymation

Risks : Irritant effects, sensitizing effects

May cause an allergic reaction Causes serious eye irritation

May cause damage to organs through prolonged

Or repeated exposure

General advice : First aid responders should pay attention to self-

protection and use the recommended protective clothing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eyes : Irrigate immediately with copious quantities of water for

several minutes. Obtain medical attention.

**Skin** : Wash immediately with copious quantities of water

with soap. Remove contaminated clothing immediately.

Obtain medical advice if skin disorders develop.

**Inhalation** : Remove from exposure, rest and keep warm and obtain

medical attention urgently. Administer oxygen or artificial respiration as needed. If breathing is irregular

or stopped, administer artificial respiration.

**Ingestion** : Wash out mouth with water. DO NOT induce vomiting.

Obtain medical attention

Indication of any immediate medical attention and special treatment needed

: Treat symptomatically

#### 5. FIRE FIGHTING MEASURES:

**Suitable Extinguishing Media** : Water/water spray/water jet/carbon dioxide/sand/foam

Alcohol resistant foam/chemical powder for extinction

**Specific Hazards** : Do not allow run-off from fire fighting to enter drains

or water courses. May release toxic, irritating and/or corrosive gases. In the event of fire and/or explosions

do not breathe fumes.



**Special Protective Precaution and** 

**Equipment** : Fire fighters to wear self-contained breathing apparatus

and suitable protective clothing

: Do not inhale explosion and /or combustion gases

: Fire residues and contaminated firefighting water must

be disposed of in accordance with local regulations

: Standard procedure for chemical fires

#### **6. ACCIDENTAL RELEASE MEASURES:**

**Personal Precautions** : Ensure adequate ventilation

: Use breathing apparatus if exposed to vapour/aerosol

Use personal protective equipmentDeny access to unprotected persons

: High risk of slipping due to leakage/spillage of product

Environmental Precautions : Prevent entry into drains, sewers and water courses.

After spillage/leakage : Prevent spread over a wide area (e.g by containment or

oil barriers

In case of product spills into drains/surface waters/ groundwater, immediately inform the authorities

Pickup with absorbent material (e.g sand, universal

absorbent, diatomaceous earth)

: Dispose of absorbed material in accordance with the

regulations

In addition, please refer to the local regulations regarding disposal.

### 7. HANDLING AND STORAGE:

**Precautions for safe handling** : Use only in well-ventilated areas

Avoid formation of aerosol

Avoid exceeding occupational exposure limits Do not eat, drink, smoke or take drugs at work

Take off contaminated clothing and wash before reuse

Wash hands before breaks and after work

Persons with a history of skin sensitisatioon problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which

this mixture is being used.

Follow standard hygiene measures when handling

chemical products



**Conditions for safe storage** : Keep only in original container

Keep container tightly closed

Keep container in a well-ventilated place
Keep in a cool place. Store in a dry place
Protect from heat/overheating and from sun
Containers which are opened must be carefully
resealed and keep upright to prevent leakage.
Store in accordance with local regulations

Hygiene measures : Handle in accordance with good industrial hygiene and

safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at

the end of the day.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION:

#### **Control Parameters**

### Occupational Exposure limits

Titanium Dioxide (>10 um): Cas.= no.: 13463-67-7: Value type (form of exposure) TWA:

Control paramaters: 10 mg/m3: Basis: DE TRGS 900

### **Engineering measures**

Maintain air concentrations below occupational exposure standards Ensure adequate ventilation, especially in confined areas.

### Personal protective equipment

Eye protection: Safety glasses with side-shields conforming to EN 166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard must be worn at all times when handling

chemical products. Nitrile rubber Neoprene Gloves

Skin Protection: Protective clothing (e.g safety shoes acc. To EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons

and protective boots are additionally recommended.

to chemicals should be ascertained with the respective supplier

Respiratory protection: Breathing apparatus in the event of high concentrations. In case

of inadequate ventilation wear respiratory protection. Ensure adequate ventilation, especially in confined areas.



General Advice: Do not flush into surface water or sanitary sewer system. If the Product contaminates rivers and lakes or drains inform Respective authorities

### 9. PHYSICAL AND CHEMICAL PROPERTIES:

Form : liquid
Colour : Greyish
Odour : pungent

Odour threshold not determined pH value not applicable pH value (1%) not applicable **Boiling point (°C)** not determined Flash point (°C) not determined Flammability (°C) not applicable Lower explosion limit not determined **Upper explosion limit** not determined

Oxidizing properties : no

Vapour pressure/gas pressure (kPa):not determinedDensity (g/ml):1.4-1.8 (25°C)Bulk Density (kg/m³):not applicablePartition coefficient (n-octanol/water):not determined

**Viscosity** : 80000 – 10000 cps (27°C)

**Relative vapour density** : not determined

determined in air

Evaporation speed : not determined Melting point (°C) : not determined Autoignition temperature (°C) : not determined Decomposition temperature (°C) : not determined

#### 10. STABILITY AND REACTIVITY:

**Reactivity** : No dangerous reactions known if used as directed

Chemical stability : Chemically stable

**Possibility of hazardous reactions** : Stable under recommended storage conditions

Conditions to avoid : No data available

Hazardous Decomposition : No decomposition if stored and applied as per

**products** recommendation



Hazardous reaction : No dangerous reaction known under conditions of

normal use

#### 11. TOXICOLOGICAL INFORMATION:

Information of toxicological effects as defied in regulation (EC) n0 1272/2008

**Acute toxicity** : Not classified due to lack of data

Components:DiethylmethylbenzenediamineAcute oral toxicity:LD50 Oral (rat): 738 mg/kg

Acute toxicity estimate: 738 mg/kg

Method: calculation method

Acute dermal toxicity : LD50 Dermal (rat): 2.500 mg/kg

Skin corrosion/irritation : Not classified due to lack of data
Serious eye damage/eye irritation : Causes serious eye irritation
Skin Sensitisation : May cause allergic skin reaction
Respiratory sensitisation : Not classified due to lack of data
Germ cell mutagenicity : Not classified due to lack of data
Carcinogenity : Not classified due to lack of data
STOT -single exposure : Not classified due to lack of data

STOT – repeated exposure : May cause damage to organs through prolonged or

repeated exposure

### 12. ECOLOGICAL INFORMATION:

**Ecotoxicity** : No data is available on the product itself

### 13. DISPOSAL CONSIDERATIONS:

Disposal must be in accordance with local and national legislation.

**Disposal** : Waste material must be disposed of in accordance with

the national and local regulations. Uncontaminated

packaging maybe taken for recycling.

The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product

residues

Packaging that cannot be cleaned should be disposed of

as for product



#### 14. TRANSPORT INFORMATION:

**UN** proper shipping name

ADR/IMDG/IATA : UN 3082

: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID

N.O.S (diethylmethylbenzenediamine)

**Transport Classes:** 

ADR/IMDG/IATA : class 9

Packing group

ADR/IMDG/IATA : III

#### 15. REGULATORY INFORMATION:

**REACH – List of substances subject to authorization** : Not applicable

Regulation (EC) No 1005/2009 on substances

that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic

Pollutant (recast) : Not applicable

SARA Section 311/312 Hazard Categories : Acute toxicity (any route of exposure)

Specific target organ toxicity (single or

Repeated exposure)

Serious eye damage or eye irritation

SARA 313 : This material does not contain any

chemical components with known CAS numbers that exceed the threshold Reporting levels established by SARA

Title III, section 313



#### **16. OTHER INFORMATION:**

The data and advice given apply when the product is used for the stated application or applications. The product is not sold as suitable for any other applications. Use of the product for applications other than as stated in the sheet may give rise to risks not mentioned in this sheet. The product should not be used other than for the stated application or applications without seeking advice from MATEX.

If the product has been purchased for supply to a third party for use at work, it is the purchaser's duty to take all necessary steps to ensure that any person handling of using the product is provided with the information in this sheet.

It is the responsibility and duty of the employer to inform employees and others who may be affected of hazards described in this sheet and of any precautions which should be taken.

This sheet does not constitute or substitute for the user's own assessment of workplace risk, as required by other health and safety legislation.

Further copies of this Safety Data Sheet may be obtained from MATEX.

MATEX Rev-00-1024



#### NON HAZARDOUS – CHEMICAL IDENTIFICATION CODE NOT APPLICABLE

### 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY UNDERTAKING:

Product Name : HYDROTHANE WP2 PLUS, PART B

HS Code : 32089000

**Application**: Elastomeric Two Part Cold Applied Polyurea

Waterproofing Membrane

Manufacturer : MATEX CONSTRUCTION CHEMICALS

MANUFACTURING CO. L.L.C.

 Address
 :
 P.O. Box 29585

 Telephone
 :
 +971 4 3334140

 Fax
 :
 +971 4 3334115

 Email
 :
 info@matex.ae

Website : www.matex-global.com

#### 2. HAZARDS IDENTIFICATION:

Classification of the substance or mixture Classification (Regulation EC no. 1272/2008

Acute Tox. 4: H332 Harmful if inhaled

Respiratory sensitisation, cat. 1 H334: May cause allergy or asthma symptoms or

breathing difficulties if inhaled

Skin sensitisation, cat. 1 H317: May cause an allergic skin reaction

Label Elements: The product is classified and required to be labelled in accordance with EC-directives Labelling according to Regulation (EC) 1272/2008

Hazard Pictograms





Signal Word Danger

Hazard Statements H317 May cause an allergic skin reaction

H332 Harmful if inhaled

H334 May cause allergy or asthma symptoms or breathing difficulties

If inhaled

**Precautionary Statements** 

P260 Do not breathe vapours/spray
P261 Avoid breathing mist or vapours



P280 Wear protective gloves/protective clothing/eye protection/face protection

P284 In case of inadequate ventilation wear respiratory protection P302+P352 IF ON SKIN: Wash with plenty of water/soap P304+P340+312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes Remove contact lenses, present and easy to do. Continue rinsing P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor

**Special labelling** Contains isocyanates. May produce an allergic reaction **Other Hazards** Further hazards were not determined with the current level of knowledge

### 3. COMPOSITION / INFORMATION ON INGREDIENTS:

The product is a mixture.

INGREDIENTS:			
Name	% Composition	CAS No.	
Aromatic Isocyanate Prepolymer	60-70	37273-56-6	
Filler	25-35	14808-60-7	
Additives	1-5	proprietary	

### 4. FIRST AID MEASURES:

#### Most Important Symptom(s) Effect(s)

Acute: Isocyanate vapors or mist at concentrations above the exposure limits or guidelines can irritate (burning sensation) the mucous membranes in the respiratory tract (nose, throat, lungs) with symptoms of runny nose, sore throat, coughing, chest discomfort, shortness of breath and reduced lung function (breathing difficulty). Persons with a preexisting, nonspecific bronchial hyperactivity can respond to concentrations below the exposure limits or guidelines with similar symptoms as well as asthma attack or asthma-like symptoms. Exposure well above the exposure limits or guidelines may lead to bronchitis, bronchial spasm and pulmonary edema (fluid in lungs). Chemical or hypersensitivity pneumonitis, with flu-like symptoms



(e.g fever, chills), has also been reported. These symptoms can be delayed up to several hours after exposure. These effects are usually reversible.

May cause skin irritation with symptoms of reddening, itching and swelling. Can cause sensitisation. Persons previously sensitized can experience allergic skin reaction with symptoms of reddening, itching, swelling and rash. Cured material is difficult to remove.

Causes serious eye irritation with symptoms of reddening, tearing, swelling and burning. May cause temporary corneal injury. Vapor or aerosol may cause irritation with symptoms of burning and tearing.

May cause irritation of the digestive tract. Symptoms may include abdominal pain, nausea, vomiting and diarrhea.

Delayed: symptoms affecting the respiratory tract can also occur several hours after Exposure.

Eyes : Irrigate immediately with copious quantities of water for

several minutes. Use lukewarm water if possible. Obtain

medical attention.

**Skin** : Wash immediately with copious quantities of water

with soap. Remove contaminated clothing immediately.

Obtain medical advice if skin disorders develop.

**Inhalation** : Remove from exposure, rest and keep warm and obtain

medical attention urgently. Administer oxygen or artificial respiration as needed. Asthmatic symptoms may develop and may be immediate or delayed up to

several hours.

**Ingestion** : Wash out mouth with water. DO NOT induce vomiting.

Obtain medical attention

Most important symptoms and effects (both acute and delayed)

Irritant effects, allergic reactions, redness, gastro-

Intestinal complaints, cough, respiratory disorder,

asthmatic appearance

Indication of any immediate medical attention and special treatment needed

: Treat symptomatically



#### 5. FIRE FIGHTING MEASURES:

**Suitable Extinguishing Media** : Water/water spray/water jet/carbon dioxide/sand/foam

Alcohol resistant foam/chemical powder for extinction

Specific Hazards : No hazardous combustion products are known

**Special Protective Precaution and** 

**Equipment**: Fire fighters to wear self-contained breathing apparatus

and suitable protective clothing

: Do not inhale explosion and /or combustion gases

Fire residues and contaminated firefighting water must

be disposed of in accordance with local regulations

: Standard procedure for chemical fires

#### 6. ACCIDENTAL RELEASE MEASURES:

**Personal Precautions** : Ensure adequate ventilation

: Use breathing apparatus if exposed to vapour/aerosol

Use personal protective equipment
Deny access to unprotected persons

: High risk of slipping due to leakage/spillage of product

**Environmental Precautions** : Prevent entry into drains, sewers and water courses. **After spillage/leakage** : Prevent spread over a wide area (e.g by containment or

oil barriers

In case of product spills into drains/surface waters/ groundwater, immediately inform the authorities Pickup with absorbent material (e.g sand, universal

absorbent, diatomaceous earth)

: Dispose of absorbed material in accordance with the

regulations

In addition, please refer to the local regulations regarding disposal.

#### 7. HANDLING AND STORAGE:

Precautions for safe handling : Use only in well-ventilated areas

Avoid formation of aerosol

Avoid exceeding occupational exposure limits

Do not eat, drink, smoke or take drugs at work

Take off contaminated clothing and wash before reuse



Wash hands before breaks and after work

Persons with a history of skin sensitisatioon problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which

this mixture is being used.

Follow standard hygiene measures when handling

Chemical products

**Conditions for safe storag** : Keep only in original container

Keep container tightly closed

Keep container in a well-ventilated place
Keep in a cool place. Store in a dry place
Protect from heat/overheating and from sun
Containers which are opened must be carefully
resealed and keep upright to prevent leakage.
Store in accordance with local regulations

No decomposition if stored and applied as directed

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION:

#### **Control Parameters**

### **Industrial Hygiene/Ventilation Measures**

Local exhaust should be used to maintain levels below the TLV and PEL whenever diisocyanate is handled, processed or spray applied. At normal room temperatures TDI Levels quickly exceed the TLV or PEL unless properly ventilated. Standard reference sources regarding industrial ventilation (e.g ACGIH Industrial Ventilation Manual) should be consulted for guidance about adequate ventilation. To ensure that published exposure limits have not been exceeded, monitoring for airborne diisocyanate should become part of the overall employee exposure characterization program. NIOSH, OSHA and others can be consulted.

#### **Engineering measures**

Maintain air concentrations below occupational exposure standards Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

Eye protection: Safety glasses with side-shields conforming to EN 166

Eye wash bottle with pure water

Hand protection: Chemical-resistant, impervious gloves complying with an

approved standard must be worn at all times when handling

chemical products.



Skin Protection: Protective clothing (e.g safety shoes acc. To EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons

and protective boots are additionally recommended.

to chemicals should be ascertained with the respective supplier

Respiratory protection: Breathing apparatus in the event of high concentrations. In case

of inadequate ventilation wear respiratory protection. Ensure adequate ventilation, especially in confined areas.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES:

Form : liquid
Colour : Yellowish
Odour : mild

**Odour threshold** not determined pH value not applicable pH value (1%) not applicable Boiling point (°C) not determined Flash point (°C) not determined Flammability (°C) not applicable Lower explosion limit not determined **Upper explosion limit** not determined

Oxidizing properties : no

**Viscosity** : 1000 – 3000 mPas (27°C)

**Relative vapour density** : not determined

determined in air

Evaporation speed:not determinedMelting point (°C):not determinedAutoignition temperature (°C):not determinedDecomposition temperature (°C):not determined

### 10. STABILITY AND REACTIVITY:

**Reactivity** : No dangerous reactions known if used as directed

**Chemical stability** : Chemically stable

Possibility of hazardous reactions : No hazards to be specially mentioned



Conditions to avoid : No data available

Hazardous Decomposition : No decomposition if stored and applied as per

**products** recommendation

**Hazardous reaction** : Materials that react with isocyanates may cause

polymerization. Moisture (water ang high humidity) or high heat can cause pressure build up with possible

explosive rupture.

#### 11. TOXICOLOGICAL INFORMATION:

Information of toxicological effects

Acute toxicity : Harmful if inhaled

Serious eye damage/irritation : Not classified due to lack of data Skin sensitisation : May cause an allergic reaction

Respiratory sensitisation : May cause allergy or asthma or breathing difficulties

If inhaled

Specific target organ toxicity

Single exposure : Not classified due to lack of data

Specific target organ toxicity

Repeated exposure : Not classified due to lack of data

Mutagenicity : no classification Reproduction toxicity : no classification

Carcinogenity : limited evidence of a carcinogenic effect

### **Toxicity data for: Aromatic Polyisocyanate Prepolymer**

**Toxicity Note** : Data is based on similar product

Acute oral toxicity : LD50: > 5,000 mg/kg (rat)

Acute inhalation toxicity : LC50: > 3.82 mg/l, 4 h, dust/mist (rat)

**Skin Irritation** : rabbit, slight irritant. Toxicological studies of

a comparable product

**Eye irritation**: rabbit, irritating. Toxicological studies of a comparable

**Product** 

**Sensitisation** : positive (Guinea pig). Toxicological studies of a

comparable product



#### 12. ECOLOGICAL INFORMATION:

**Ecological Data for Aromatic Polyisocyanate Prepolymer** 

**Biodegradation**: Not readily biodegradable. Ecotoxicological reports on a

comparable product

Acute and prolonged toxicity to fish : No toxic effects with saturated solution: (Danto rerio

(Zebra fish), 96h). Ecotoxicological reports on a

comparable product

**Acute toxicity to aquatic invertebrates**: No toxic effects with saturated solution: (Daphnia magna

(water flea), 48h). Ecotoxicological reports on a

comparable product

**Toxicity to aquatic plants** : No toxic effects with saturated solution: (Scenedesmus

Subspicatus, 72h). Ecotoxicological reports on a

comparable product

**Toxicity to microorganisms** : EC50: >10,000 mg/l, (activated sludge). Ecotoxicological

reports on a comparable product

**Additional ecotoxicological remarks**: Data is based on a similar product

#### 13. DISPOSAL CONSIDERATIONS:

Disposal must be in accordance with local and national legislation.

**Disposal** : Waste material must be disposed of in accordance with

the national and local regulations. Uncontaminated

packaging maybe taken for recycling.

The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product

residues

Packaging that cannot be cleaned should be disposed of

as for product

### 14. TRANSPORT INFORMATION:

**UN proper shipping name** 

Transport by land according to ADR/RID: NOT REGULATED AS DANGEROUS GOODS

Marine transport in accordance with

IMDG : NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA : NOT CLASSIFIED AS "DANGEROUS GOODS"



#### 15. REGULATORY INFORMATION:

**REACH – List of substances subject to authorization**: Not applicable

Regulation (EC) No 1005/2009 on substances

that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic

Pollutant (recast) : Not applicable

SARA Section 311/312 Hazard Categories : Refer to hazard classification

Information in section 2

#### **16. OTHER INFORMATION:**

The data and advice given apply when the product is used for the stated application or applications. The product is not sold as suitable for any other applications. Use of the product for applications other than as stated in the sheet may give rise to risks not mentioned in this sheet. The product should not be used other than for the stated application or applications without seeking advice from MATEX.

If the product has been purchased for supply to a third party for use at work, it is the purchaser's duty to take all necessary steps to ensure that any person handling of using the product is provided with the information in this sheet.

It is the responsibility and duty of the employer to inform employees and others who may be affected of hazards described in this sheet and of any precautions which should be taken.

This sheet does not constitute or substitute for the user's own assessment of workplace risk, as required by other health and safety legislation.

Further copies of this Safety Data Sheet may be obtained from MATEX.

MATEX Rev-00-1024