

Material Safety Data Sheet


NON HAZARDOUS – CHEMICAL IDENTIFICATION CODE NOT APPLICABLE

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY UNDERTAKING:

Product Name : HYDROTHANE PU2 CLEAR, PART A
HS Code : **32089000**
Application : Elastomeric Two-part Polyurethane Clear Waterproofing Membrane
Manufacturer : MATEX CONSTRUCTION CHEMICALS MANUFACTURING CO. L.L.C.
Address : P.O. Box 29585
Telephone : +971 4 3334140
Fax : +971 4 3334115
Email : info@matex.ae
Website : www.matex-global.com

2. HAZARDS IDENTIFICATION:

Environment hazardous



Harmful if inhaled

3. COMPOSITION / INFORMATION ON INGREDIENTS:

Ingredients	% Composition	CAS No.
Branched polyalcohol	40-60	109-17-1
Xylene	20-25	108-38-3
Filler	25-30	14808-60-7
Additive	1-5	3586-55-8

4. FIRST AID MEASURES:

Skin contact : Flush with large amounts of clean water, use soap available.
Remove any contaminated clothing.
Eye contact : Check for and remove any contact lenses. Flush with large

Material Safety Data Sheet

amounts of clean warm water for 15 minutes. Get prompt medical attention.

Inhalation : Immediately move victim to fresh air. If breathing has stopped then administer artificial respiration. Get prompt medical attention.

5. FIRE FIGHTING MEASURES:

Suitable Extinguishing Media:	CO ₂ / Dry chemical powder. Do not use water jets.
Special Protective Equipment:	Self - contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES:

Personal precautions	Remove ignition sources. Provide for sufficient ventilation. Do not inhale the vapour. Refer to protective measures listed in sections 7 and 8.
Environmental precautions	Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.
Methods for cleaning up/collecting	Contain and collect spillage with non-combustible Absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent; avoid use of solvents.

7. HANDLING AND STORAGE:

Information for safe handling	Prevent the creation of inflammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the OEL (=Occupational Exposure Limit). Additionally, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing. No sparking tools should be used. Avoid contact with skin and eyes. Do not inhale the vapour. Do not eat or drink during work – no smoking. Comply with the health and safety at work laws.
-------------------------------	--

Material Safety Data Sheet

Information about protection against
Explosions and fires

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

Requirements to be met by storerooms
And containers

Keep container tightly closed. Never use pressure to empty; container is not a pressure vessel. No smoking. Prevent unauthorized access.

Information about separation of
Incompatible products

Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Further information about
storage conditions

Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.

Storage class (VCI)

Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Keep away from ignition sources - No smoking.
3A

8. EXPOSURE CONTROLS / PERSONAL PROTECTION:

Occupational Exposure Limits	:	None assigned
Engineering Control Measures	:	Use with adequate general and local exhaust ventilation
Personal Protective Equipment	:	Impervious gloves, safety goggles, plastic apron.

9. PHYSICAL AND CHEMICAL PROPERTIES:

Form	:	Liquid
Colour	:	Transparent
Odour	:	Aromatic
Change in physical state	:	N/A
Boiling point, °C(mm Hg)	:	N/A
Melting point, °C	:	< 0 °C
Flash Point (°C)	:	> 60 °C
Thermal decomposition	:	N/A
Specific gravity (°C)	:	1.1 (25)
pH value (°C)	:	N/A
Solubility in water (°C)	:	N/A

Material Safety Data Sheet

10. STABILITY AND REACTIVITY:

Conditions to avoid	:	Stable under recommended storage and handling conditions (See section 7).
Materials to avoid	:	Keep away from oxidizing agents, strongly alkaline and Strongly acid materials in order to avoid exothermic reactions. Exothermic reaction with amines and alcohols. In contact with water (moisture) CO ₂ is formed which leads to an excess pressure in closed containers.

11. TOXICOLOGICAL INFORMATION:

There are no data available on the preparation itself. This has been assessed following the conventional method of the Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly.

Based on the properties of the epoxy constituent(s) and considering toxicological data on similar preparations, this product may be a skin sensitizer and irritant. May produce allergic reactions.
LD50 oral, rat: >2000 mg/kg

12. ECOLOGICAL INFORMATION:

	Contaminated packaging must be emptied of all residues and, following appropriate cleaning, may be sent to a recycling plant. Uncleaned packaging must be disposed of in the same manner as the medium.
Product Waste key	Disposal Code according to European Waste Catalog (EWC) please specify according to the use of product, e.g.: 080102 Waste from production, formulation, sales and application of paints and varnishes. Old paints and varnishes, not containing halogenated hydrocarbons. Switzerland: Disposal code (VVS): 1620 Waste from paints, varnishes and adhesives with organic phase or solvent

13. DISPOSAL CONSIDERATIONS:

Proper shipping name:	Resin solution, flammable
UN Number:	1866

Material Safety Data Sheet

Class : 3
 Subsidiary risk: -
 Packing Group: I
 Label(s):



Additional Information

ADR-HIN : 30
 IMDG-EMS : F-E, S-E Marine Pollutant: Yes
 IMO : -

14. REGULATORY INFORMATION:

Labelling	Labelling according to EEC directives concerning preparations.
R-phrases	R10 Flammable
S-phrases	R51 Use only in well-ventilated areas.
National regulatory information	Regulation on inflammable liquids (VbF) VbF-Class : Not dangerous according to VbF
Emission control act ("TA-Luft")	Sum organic substances class II : < 5 % Sum organic substances class III : 25 - 30 %
Water pollution classification	Class : 1 according VwVwS
Poisonous law (CH)	Giftklasse: frei, BAGT-Nr: 619 000
Denmark	Denmark: PR-Nr. : 899758 MAL-Code: 3-1 MAL-Code for ready mixture: 3-3
Other regulations	Observe UVV for handling of painting material (VBG 23). Germany: Refer also to: "Solvents". (BG-Chemie, Guideline M 017, ZH 1/319). Switzerland: Please refer to the guidelines of SUVA and EKAS. e.g.: "Guideline for preventing accidents when using two component resins" (SUVA 1854)

15. OTHER INFORMATION:

The data and advice given apply when the product is used for the stated application or applications. The product is not sold as suitable for any other applications. Use of the product for applications other than as stated in the sheet may give rise to risks not mentioned in this sheet. The product should not be used other than for the stated application or applications without seeking advice from MATEX.

Material Safety Data Sheet

If the product has been purchased for supply to a third party for use at work, it is the purchaser's duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet.

It is the responsibility and duty of the employer to inform employees and others who may be affected of hazards described in this sheet and of any precautions which should be taken.

This sheet does not constitute or substitute for the user's own assessment of workplace risk, as required by other health and safety legislation.

Further copies of this Safety Data Sheet may be obtained from MATEX.

Material Safety Data Sheet

NON HAZARDOUS – CHEMICAL IDENTIFICATION CODE NOT APPLICABLE

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY UNDERTAKING:

Product Name	:	HYDROTHANE PU2 CLEAR, PART B
HS Code	:	32089000
Application	:	Elastomeric Two-part Polyurethane Clear Waterproofing membrane
Manufacturer	:	MATEX CONSTRUCTION CHEMICALS MANUFACTURING CO. L.L.C.
Address	:	P.O. Box 29585
Telephone	:	+971 4 3334140
Fax	:	+971 4 3334115
Email	:	info@matex.ae
Website	:	www.matex-global.com

2. HAZARDS IDENTIFICATION:

Classification of the Chemicals:

Flammable 3	:	Flammable material
Acute Toxicity 4	:	Harmful in contact with skin and if inhaled
Specific Target	:	Respiratory Tract Irritation
Organ toxicity		
CAT. 4		

Warning

Flammable.

Harmful by inhalation.

Irritating to respiratory system.

May cause sensitization by skin contact.

Hazard statements:

H226	Flammable liquid and vapour.
H332	Harmful if inhaled.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H312	Harmful in contact with skin

Precautionary statements:

P210 Keep away from heat/sparks/ open flames/hot surface – NO SMOKING
P233 Keep container tightly closed

Material Safety Data Sheet

P280 Wear protective gloves / protective clothing / eye protection
P333+P313 If skin irritation or rash occurs, get medical attention
P370 + P378 In case of fire, use powder or CO₂ for extinction
P501 Dispose of contents/ container in accordance with applicable regulations.

Special Provisions:

EUH204 Contains isocyanates. May produce an allergic reaction.

Contents:

HDI obligomers, isocyanurate
Hexamethylene-di-isocyanate

Others Hazards:

vPvB Substances: None – PBT Substances: None

3. COMPOSITION / INFORMATION ON INGREDIENTS:

Ingredients	% Composition	CAS No.	Classification	Specific Concentration Limits M- Factors
HDI Oligomers	90	28182-81-2	H 332 – Acute Toxicity 4 H 317- Skin Sensitization H 335 – STOT SE 3	STOT SE3 : C _≥ 5% Skin Irritant 2 : C _≥ 5% Resp. Sense 1 : C _≥ 1%
Aromatic Hydrocarbon solvents	To 10	1330-20-7	Flam. Liq. 3 H 226 GHS 02 Acute Toxicity H 312 GHS 07 Skin Irritation 2 H 315 Warning	

4. FIRST AID MEASURES:

Skin contact : Flush with large amounts of clean water, use soap if available.
Remove any contaminated clothing.

Eye contact : Check for and remove any contact lenses. Flush with large amounts of clean warm water for 15 minutes. Get prompt medical attention.

Inhalation : Immediately move victim to fresh air. If breathing has stopped then administer artificial respiration. Get prompt medical attention.

Material Safety Data Sheet

5. FIRE FIGHTING MEASURES:

Suitable Extinguishing Media:	Fire extinguishing powder, foam or CO ₂ . Use foam and water jets only in case of extensive fire outbreak. Extinguishing media which must not be used for safety reasons: high volume water jet.
Special Hazards arising From the substance or mixture:	Do not inhale explosion and combustion gases. Burning releases carbon monoxide, carbon dioxide, oxides of nitrogen, isocyanate vapors and traces of hydrogen cyanide.
Advice for fire-fighters:	During the extinction of fires it is necessary to protect the airway with a breathing apparatus and protective clothing resistant to chemicals. Collect contaminated fire extinguishing water separately. This must be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES:

Personal precautions	Remove ignition sources. Provide for sufficient ventilation. Do not inhale the vapour. Refer to protective measures listed in sections 7 and 8.
Environmental precautions	Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.
Methods for cleaning up/collecting	Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent; avoid use of solvents.

7. HANDLING AND STORAGE:

Information for safe handling	Prevent the creation of inflammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the OEL (=Occupational Exposure Limit). Additionally, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another.
-------------------------------	--

Material Safety Data Sheet

Information about protection against Explosions and fires	Operators should wear antistatic footwear and clothing. No sparking tools should be used. Avoid contact with skin and eyes. Do not inhale the vapour. Do not eat or drink during work – no smoking. Comply with the health and safety at work laws.
Requirements to be met by storerooms And containers	Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. No smoking.
Information about separation of Incompatible products	Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.
Further information about storage conditions	Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Keep away from ignition sources - No smoking.
Storage class (VCI)	3A

8. EXPOSURE CONTROLS / PERSONAL PROTECTION:

Control parameters	:	n-butyl acetate – CAS: 123-86-4 TLV TWA: 150 ppm 713 mg/m ³ TLV STEL: 200 ppm – 950, 18 mg/m ³ Hexamethylene-di-isocyanate – CAS: 822-06-0 TLV TWA: 0.005 ppm 0.034 mg/m ³ DNEL Exposure limit values N.A. PNEC Exposure limit values N.A.
Exposure Controls		
Eye Protection	:	Use safety goggles of close fitting safety goggles, don't use eye lens
Skin Protection	:	Wear suitable protective clothing
Hand Protection	:	Use protective gloves that provides comprehensive protection,

Material Safety Data Sheet

Respiratory protection : e.g. PVC neoprene or rubber
In places with poor ventilation and during the spraying process it is necessary to protect the respiratory tract. It is recommended to wear a mask with air supply or a mask with combination filter A2-P2 FOR short-term jobs.
In case of hypersensitivity of the respiratory tract (e.g. asthmatics and those who suffer from chronic bronchitis) it is inadvisable to work with the product.
Symptoms affecting the respiratory tract can also occur several hours after overexposure.

9. PHYSICAL AND CHEMICAL PROPERTIES:

Appearance : Clear Liquid
Odour : of solvent
Boiling point : 126°C
Vapour density : >1
Flash point : 25°C
Vapour pressure : 1,5 kPa @ 20°C
Relative density : 1,13 g/cm³
Solubility in water : Insoluble, REACTS WITH WATER

10. STABILITY AND REACTIVITY:

Conditions to avoid : Stable under recommended storage and handling conditions (See section 7).
Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reaction with amines and alcohols. In contact with water (moisture CO₂ is formed which leads to an excess pressure in closed containers).

11. TOXICOLOGICAL INFORMATION:

This product may be an irritant. May produce inflammatory reactions on inhalation.

Material Safety Data Sheet

12. ECOLOGICAL INFORMATION:

Is converted in connection with water in a solid, insoluble and inert polyurea, liberating CO₂.

Additional ecological information

General ecological information Do not empty into waters or drains.

13. DISPOSAL CONSIDERATIONS:

Product Waste key	Contaminated packaging must be emptied of all residues and, following appropriate cleaning, may be sent to a recycling plant. Uncleaned packaging must be disposed of in the same manner as the medium. Disposal Code according to European Waste Catalog (EWC) please specify according to the use of product, e.g.: 080102 Waste from production, formulation, sales and application of paints and varnishes. Old paints and varnishes, not containing halogenated hydrocarbons. Switzerland: Disposal code (VVS): 1620 Waste from paints, varnishes and adhesives with organic phase or solvent.
-------------------	---

14. TRANSPORT INFORMATION:

Proper shipping name:	Polyisocyanate curing agent
UN Number (ADR/RID/ADN):	1866
Class:	3
Packing Group:	III
Label(s):	3
IMDG:	
ONU Number:	1866
Class:	3
Packing Group:	III
Dangerous Labels:	3
Marine Pollutant:	No
ICAO:	
ONU Number:	1866
Class:	3
Packing Group:	III
Dangerous Labels:	3

15. REGULATORY INFORMATION:

Material Safety Data Sheet

Labelling

Labelling according to EEC directives concerning preparations.
Xn ; Harmful

H332 Harmful if inhaled
H317 May cause an allergic skin reaction
H335 May cause respiratory irritation
H226 Flammable liquid and vapour
H336 May cause drowsiness or dizziness
H319 Causes serious eye irritation
H315 Causes skin irritation
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled
H331 Toxic if inhaled
P210 Keep away from heat/sparks/open flames/hot surface – NO SMOKING
P233 Keep container tightly closed
P280 Wear protective gloves / protective clothing / eye protection
P333 + P313 If skin irritation or rash occurs, get medical attention
P370 + P378 In case of fire, use powder or CO₂ for extinction
P501 Dispose of contents/ container in accordance with applicable regulations.

Registration Status

Chemical : TSCA - released/ listed
AICS - released/ listed
DSL - released/ listed

HMIS Rating : Health: 1, Flammability: 2, Physical Hazard: 0

H223 Flammable material
H316 Causes skin irritation
H312 Harmful in contact with skin
H332 Harmful if inhaled
H336 May cause drowsiness or dizziness

16. OTHER INFORMATION:

The data and advice given apply when the product is used for the stated application or applications. The product is not sold as suitable for any other applications. Use of the product for applications other than as stated in the sheet may give rise to risks not mentioned in this sheet. The product should not be used other than for the stated application or applications without seeking advice from MATEX.

Material Safety Data Sheet

If the product has been purchased for supply to a third party for use at work, it is the purchaser's duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet.

It is the responsibility and duty of the employer to inform employees and others who may be affected of hazards described in this sheet and of any precautions which should be taken.

This sheet does not constitute or substitute for the users own assessment of workplace risk, as required by other health and safety legislation.

Further copies of this Safety Data Sheet may be obtained from MATEX.